

ATTESTATION

of conformity with European Directives

BV LCIE CHINA Number 2466AS04CNQV54305

Product Hybrid Inverter

Reference SSE-HH12K-P3EU, SSE-HH10K-P3EU, SSE-HH8K-P3EU

Issued to Shenzhen Sosen Innovation Technology Co Ltd

Address 601, Pengzhanhui, Building 1, No.233, Xinqiao Community Center Road, Xinqiao Street,

Bao'an District, Shenzhen, China

Manufacturer Shenzhen Sosen Innovation Technology Co Ltd

Technical characteristics See below table

The submitted sample of the above equipment has been tested for C marking according to following European Directive and following standards:

LVD Directive 2014/35/EU *

* Thanks to note that from April 20th 2016; this directive will be replaced by the new LVD directive, 2014/35/EU.

Standards	Report number	Report date
IEC 62109-1:2010/EN 62109-1:2010	CNQV-ESH-P24010319-1	2024-04-17
IEC 62109-2:2011/EN 62109-2:2011	CNQV-ESH-P24010319-2	2024-04-17

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

The CE marking may be affixed if all relevant and effective European Directives with CE are applicable

Shanghai (P.R. China), April 17th, 2024



Product Line Manager

This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.

Version: 3.0 / Feb.10, 2021



Model / Type:	SSE-HH8K-P3EU	SSE-HH10K-P3EU	SSE-HH12K-P3EU
MPP DC voltage range [V]:	5	150-950	
Max. Input DC voltage [V]:	V (3)	1000	M. S
Max. Input DC current [A]:	16/16		
Battery DC voltage range [V]:	125-800		
Max.charge/discharge DC current [A]:	40		
Output AC voltage [V]:	400/230,50Hz		
Max. Output AC current [A]	11,6	14,5	17,4
Rated output power [VA]:	8000	10000	12000

Page 2 of 2